



CERTIFICATE

No. Z2 118443 0037 Rev. 25

Holder of Certificate: **Jinko Solar Co., Ltd.**

No.1, Yingbin Avenue
Shangrao Economic and Technological Development Zone
334100 Shangrao City, Jiangxi Province
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product:

Crystalline Silicon Terrestrial Photovoltaic (PV) Modules
Mono-Crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 704062307437-25

Valid until: 2031-05-13

Date, 2026-05-21

(Zhulin Zhang)



CERTIFICATE

No. Z2 118443 0037 Rev. 25

Model(s):

JKMxxxN-78HL4-BDV, JKMxxxN-78HL4-BDV-J,
JKMxxxN-78HL4-BDV-IN, JKMxxxN-78HL4-BDV-IN1,
JKMxxxN-78HL4-BDV-S, JKMxxxN-78HL4-BDV-S1,
JKMxxxN-78HL4-BDV-S2, (xxx=600-665, in steps of 5)
JKMxxxN-72HL4-BDV, JKMxxxN-72HL4-BDV-J,
JKMxxxN-72HL4-BDV-U, JKMxxxN-72HL4-BDX,
JKMxxxN-72HL4-BDV-IN, JKMxxxN-72HL4-BDV-IN1
(xxx=560-610, in steps of 5)
JKBSxxxN-48HL4-BDV (xxx=375-390, in steps of 5)
JKMxxxM-72HL4-BDVP, JKMxxxM-72HL4-BDVP-J
(xxx=540-560, in steps of 5)
JKMxxxN-66HL4M-BDV, JKMxxxN-66HL4M-BDX,
JKMxxxN-66HL4M-BDV-IN, JKMxxxN-66HL4M-BDV-S,
JKMxxxN-66HL4M-BDV-S1, JKMxxxN-66HL4M-BDV-S2
(xxx=590-655, in steps of 5)
JKMxxxN-54HL4M-BDV (xxx=495-535, in steps of 5)
JKMxxxN-48HL4M-BDV (xxx=440-475, in steps of 5)
JKMxxxN-54HL4R-BDV, JKMxxxN-54HL4R-BDB
(xxx=420-460, in steps of 5)
JKxxxN-66H5-BGV, JKMxxxN-66HL5-BDV,
JKMxxxN-66HL5-BDV-IN, JKMxxxN-66HL5-BDV-S,
JKMxxxN-66HL5-BDV-S1, JKMxxxN-66QL7-BDV
(xxx=685-760, in steps of 5)
JKBSxxxN-48HL4-BDVW (xxx=370-390, in steps of 5)
JKMxxxN-54HL4R-DB (xxx=435-455, in steps of 5)
JKMxxxN-48HL4M-DB, DMM48HL4M-xxxAG
(xxx=440-480, in steps of 5)
JKMxxxN-48HL4M-DV (xxx=440-480, in steps of 5)
JKMxxxN-66QL6-BDV (xxx=630-670, in steps of 5)
JKMxxxN-51QL6-BDV (xxx=475-510, in steps of 5)
JKMxxxN-51QL6-DV (xxx=480-515, in steps of 5)
JKMxxxN-51QL6-DB (xxx=475-510, in steps of 5)
JKMxxxN-48QL6-BDV (xxx=460-485, in steps of 5)
JKMxxxN-48QL6-DV (xxx=450-480, in steps of 5)
JKMxxxN-48QL6-DB (xxx=450-475, in steps of 5)
JKMxxxT-66HL4M-BDV (xxx=640-665, in steps of 5)
JKBTxxxN-15HL4-BDV-B0B (xxx=100-115, in steps of 5)
xxx is standing for rated output power at STC

Parameters:

Fire Safety Class:	Class C according to UL790
Safety Class:	Class II
Max. System Voltage:	1500V DC
Construction:	Framed or frameless double glass with Junction box, cable and connector.

Production Facility(ies):

115876, 113943, 116025, 119488, 075612, 120017,
121280, 115860, 122742, 118612, 119487, 125355,
134193, 130968, 136160, 105673



CERTIFICATE

No. Z2 118443 0037 Rev. 25

**Tested
according to:**

IEC 61215-1:2021
IEC 61215-1-1:2021
IEC 61215-2:2021
IEC 61730-1:2023
IEC 61730-2:2023
EN IEC 61215-1:2021
EN IEC 61215-1:2021/AC:2021
EN IEC 61215-1-1:2021
EN IEC 61215-2:2021
EN IEC 61730-1:2018
EN IEC 61730-1:2018/AC:2018-06
EN IEC 61730-2:2018
EN IEC 61730-2:2018/AC:2018-06